

left and right end of said tensioning rail, respectively; and respective adjustable screws interconnecting the respective adjustable portions to the respective secured portions.

[Please amend claim 2 as follows:

2. (Amended) The adjustable assembly of claim 1, each of said left and right secured portions having front and rear block sections connected to a base block section so as to define a space between said front and rear block section, said front and rear block sections further defining a hole in an aligned orientation so as to pass through said front and rear block sections and across the space between the front and rear block sections.

[Please amend claim 3 as follows:

3. (Amended) The adjustable assembly of claim 2, wherein each of said left and right adjustable portions include an attachment block section having an elongate threaded tension screw fixedly attached to said attachment block section and extending through said front and rear block sections spanning the space between the front and rear block sections.

[Please amend claim 4 as follows:

4. (Amended) The adjustable assembly of claim 3, further comprising a screw adjustment knob between said front and rear block section defining an inner threaded hole for receiving said threaded tension screw.

[Please amend claim 5 as follows:

5. (Amended) The adjustable assembly of claim 4, further comprising a graduated measuring scale on said left and right side rail so as to provide a measurement guide for accurate adjustment

of the respective left and right sides of the tensioning rail with respect to the left and right side rail.

[Please amend claim 6 as follows:

6. (Amended) The adjustable assembly of claim 5, wherein said hole defined by said front and rear block sections is of a larger diameter than said threaded tension screw.

[Please amend claim 7 as follows:

7. (Amended) The adjustable assembly of claim 1, wherein said left and right secured portions are fixedly connected to said left and right side rails and said left and right adjustable portions are engaged with said left and right ends of said tensioning rail.

[Please amend claim 8 as follows:

8. (Amended) An adjustable tonneau cover for a cargo box having upwardly extending left and right side walls, a front wall and a rear end gate wall, said walls defining the boundaries of the cargo box, the adjustable cover assembly comprising:-

left and right side rails connectable to said left and right side walls, respectively;

an elongate tensioning rail having left and right ends, said tensioning rail extending from said left side rail to said right side rail; and

left and right adjustable threaded screw connection mechanisms including:

left and right securing blocks; said securing blocks being connected to said left and right side rails, respectively;

left and right adjustable engaging blocks; said adjustable engaging blocks being engaged with said left and right ends of said tensioning rail, respectively; and

left and right adjustable connection mechanisms connecting the respective securing blocks to the respective adjustable engaging blocks.

[Please amend claim 9 as follows:

9. (Amended) The adjustable tonneau cover of claim 8, each of the left and right securing blocks having front and rear block sections connected to a base block section so as to define a space between the front and rear block sections, the front and rear block sections further defining openings in an aligned orientation so as to pass through both of said front and rear block sections.

[Please amend claim 10 as follows:

10. (Amended) The adjustable tonneau cover of claim 9, wherein each of said left and right adjustable engaging blocks include an attachment block section having an elongate threaded tension screw fixedly attached to said attachment block and extending through said front and rear block sections spanning the space between the front and rear block sections.

[Please amend claim 11 as follows:

11. (Amended) The adjustable tonneau cover of claim 10, further comprising a screw adjustment knob between said front and rear block sections defining an inner threaded opening for receiving said threaded tension screw.

[Please amend claim 12 as follows:

12. (Amended) The adjustable tonneau cover of claim 11, further comprising a graduated measuring scale on each of said left and right rail so as to provide a measurement guide for

accurate adjustment of said left and right ends of said tensioning rail with respect to the left and right side rails, respectively.

[Please amend claim 13 as follows:

13. (Amended) The adjustable tonneau cover of claim 12, wherein said openings defined by said front and rear block sections are of a larger diameter than said threaded tension screw.

[Please amend claim 14 as follows:

14. (Amended) The adjustable tonneau cover of claim 8, wherein said left and right securing blocks are fixedly connected to said left and right side rails, respectively, and said left and right attachment blocks are fixedly connected to the respective ends of the tensioning rail.

[Please amend claim 15 as follows:

15. (Amended) An adjustable assembly for a tonneau cover used to cover a pickup truck cargo box, the cargo box having a plurality of upwardly extending walls, said plurality of upwardly extending walls including left and right side walls, said plurality of upwardly extending walls at least partially defining an interior compartment of the cargo box, the adjustable assembly comprising:

left and right side rails connected to said left and right side walls, respectively;

an elongate tensioning rail having left and right ends, said tensioning rail extending from the left side rail to the right side rail, the tonneau cover attached to the tensioning rail; and

left and right adjustable threaded screw adjustment mechanisms, each of the respective adjustable threaded screw adjustment mechanisms having side rail securing portions connected to the respective side rails and tensioning rail engagement members engaged with said elongate tensioning rail; wherein each of said left and right side rail securing portions include a threaded screw member, and each of the threaded screw members are positioned and arranged such that a force can be placed upon the elongate tensioning rail by each of the threaded screw members as said screw member is adjustably manipulated to force the tensioning rail away from the respective side rail securing portion.

[Please amend claim 16 as follows:]

16. (Amended) The adjustable assembly of claim 15, wherein the tensioning rail includes a tensioning rail attachment chamber and each of said left and right tensioning rail engagement members is engaged within the tensioning rail attachment chamber.

[Please amend claim 17 as follows:]

17. (Amended) The adjustable assembly of claim 16, wherein each of said left and right tensioning rail engagement members extends below the side rail with which it is engaged such that the tensioning rail is restrained from being lifted away from the respective side rails when the respective engagement members are engaged with the respective side rails.

[Please amend claim 18 as follows:]

18. (Amended) The adjustable assembly of claim 15, wherein each of the threaded screw members is engaged in coaxially aligned openings in each of the respective side rail securing portions.

Please cancel claims 19-29.

Please amend claim 30 as follows:

30. (Amended) An adjustable assembly for a tonneau cover used to cover a pickup truck cargo box having a plurality of upwardly extending walls, said plurality of upwardly extending walls including left and right side walls, said plurality of upwardly extending walls at least partially defining an interior compartment of the cargo box, the adjustable assembly comprising:

left and right side rails connected to said left and right side walls, respectively;

an elongate tensioning rail having left and right ends, said elongate tensioning rail extending from said left side rail to said right side rail, the tonneau cover being attached to the elongate tensioning rail;

left and right side rail securing blocks connected to said left and right side rails, respectively; and

left and right tensioning rail engagement blocks engaged with said left and right ends of said elongate tensioning rail, respectively, and adjustably engaged with the respective side rails proximate the respective ends of the elongate tensioning rail such that the elongate tensioning rail is adjustably engaged with the opposing left and right side rails and movable with respect thereto; wherein the left and right side rail securing blocks include left and right screw members adjustably interconnecting the respective tensioning rail engagement blocks with the respective side rail securing blocks.

✓
Please cancel claim 31.

Please add the following new claim 33:

Sub
C7
C8
C9
C10
C11
C12
C13
33. (New) An adjustable tonneau cover apparatus for attachment to a cargo box of a pickup truck, the cargo box having a plurality of upwardly extending walls, said plurality of upwardly extending walls including left and right side walls, the adjustable tonneau cover apparatus comprising:

a flexible tonneau cover;

left and right side rails attachable to said left and right side walls, respectively;


left and right adjustable threaded screw attachment mechanisms secured to the left and right side rails, respectively; each of the left and right threaded screw attachment mechanisms having a secured portion, secured to the respective side rail, and an adjustable portion; wherein the adjustable portion can be moved further away from or closer to the secured portion by adjusting the respective threaded screw attachment mechanism;

a tensioning rail engaged with a first end of the flexible tonneau cover; the tensioning rail having left and right ends, which are moveable further away from the secured portion of the respective threaded screw attachment mechanism, to place a greater tension on the tonneau cover, when the left and right side rails are attached to the left and right side walls, respectively, the respective ends of the tensioning rail are engaged with the adjustable portions of the

respective adjustable threaded screw attachment mechanism and the respective adjustable threaded screw attachment mechanisms are adjusted to move the adjustable portion further away from the secured portion.

[Please add the following new claim 34:]


34. (New) The adjustable tonneau cover securing apparatus of claim 33, wherein the respective adjustable threaded screw attachment mechanisms include a screw that passes through an opening in the secured portion.

 [Please add the following new claim 35:]

35. (New) A method of maintaining an appropriate tension on a flexible tonneau cover attached to a cargo box of a pickup truck, the pickup truck cargo box having a plurality of upwardly extending walls, said plurality of upwardly extending walls including left and right side walls, said plurality of upwardly extending walls at least partially defining an interior compartment of the cargo box; the method comprising the steps of:

attaching an adjustable tonneau cover securing apparatus to the cargo box of the pickup truck, the step of attaching including securing the adjustable tonneau cover securing apparatus to left and right side walls of the cargo box; the adjustable tonneau cover securing apparatus including: left and right side rails attachable to said left and right side walls, respectively; left and right adjustable threaded screw attachment mechanisms secured to the left and right side rails, respectively; and a tensioning rail engaged with a first end of the flexible tonneau cover; each of the left and right threaded screw attachment mechanisms having a secured portion, secured to the respective left or right side rail; and an adjustable portion; wherein the adjustable

portion can be moved further away from or closer to the secured portion by adjusting the respective threaded screw attachment mechanism; the tensioning rail having left and right ends, which are moveable further away from the secured portion of the respective threaded screw attachment mechanism to place a greater tension on the tonneau cover when the left and right side rails are attached to the left and right side walls of the cargo box, respectively; the respective ends of the tensioning rail being engaged with the adjustable portions of the respective adjustable threaded screw attachment mechanism and the respective adjustable screw attachment mechanisms being adjustable to move the adjustable portion further away from the secured portion; and

 adjusting the respective adjustable threaded screw attachment mechanisms to move the adjustable portion further away from the secured portion.

[Please add the following new claim 36:]

36. (New) An adjustable assembly for a cargo box cover for use on a cargo box having upwardly extending left and right side walls, the cargo box cover having left and right side rails connected to said left and right side walls, respectively, an elongate tensioning rail having left and right ends, said elongate tensioning rail extending from said left side rail to said right side rail, and a flexible cover fixedly attached to said elongate tensioning rail, said adjustable assembly comprising:

left and right adjustable threaded screw connection mechanisms; the threaded screw connection mechanisms including respective left and right secured portions secured to said left and right side rails, respectively; respective left and right adjustable screws engaged with the

elongate tensioning rail so that the respective screws can be adjusted to force the elongated tensioning rail incrementally further away from the respective, left and right, secured portions.

[Please add the following new claim 37:]

37. (New) The adjustable assembly of claim 36, wherein said left and right secured portions are fixedly connected to said left and right side rails and said left and right adjustable portions are engaged with said left and right ends of said tensioning rail.

B21 [Please add the following new claim 38:]

38. (New) An adjustable assembly for a tonneau cover used to cover a pickup truck cargo box, the cargo box having a plurality of upwardly extending walls, said plurality of upwardly extending walls including left and right side walls, said plurality of upwardly extending walls at least partially defining an interior compartment of the cargo box, the adjustable assembly comprising:

left and right side rails connected to said left and right side walls, respectively;

an elongate tensioning rail having left and right ends, said tensioning rail extending from the left side rail to the right side rail, the tonneau cover attached to the tensioning rail; and

left and right adjustable threaded screw adjustment mechanisms, each of the respective adjustable threaded screw adjustment mechanisms having side rail securing portions connected to the respective side rails; wherein each of said left and right side rail securing portions include a threaded screw member, and each of the threaded screw members are positioned and arranged

BA such that a force can be placed upon the elongate tensioning rail by each of the threaded screw members as said screw member is adjustably manipulated to force the tensioning rail away from the respective side rail/securing portion.
